

Technical parameters							
Model(s):		Outdoor unit: MHA-V8W/D2N8-B2 Indoor unit: HB-A100/C***GN8-B2, HBT-A100/190CD***GN8-B2, HBT-A100/240CD***GN8-B2					
Air-to-water heat pump:		YES					
Water-to-water heat pump:		NO					
Brine-to-water heat pump:		NO					
Low-temperature heat pump:		NO					
Equipped with a supplementary heater:		YES					
Heat pump combination heater:		YES					
Declared climate condition:		AVERAGE					
Parameters are declared for medium-temperature application.							
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	6.6	kW	Seasonal space heating energy efficiency	ηs	131.5	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7℃	Pdh	5.84	kW	Tj = -7℃	COPd	2.16	-
Tj = 2℃	Pdh	3.75	kW	Tj = 2℃	COPd	3.30	-
Tj = 7℃	Pdh	2.42	kW	Tj = 7℃	COPd	4.34	-
Tj = 12℃	Pdh	1.39	kW	Tj = 12℃	COPd	5.33	-
Tj = bivalent temperature	Pdh	5.84	kW	Tj = bivalent temperature	COPd	2.16	-
Tj = operating limit	Pdh	4.90	kW	Tj = operating limit	COPd	1.84	-
For air-to-water heat pumps: Tj = -15℃	Pdh	-	kW	For air-to-water heat pumps: Tj = -15℃	COPd	-	-
Bivalent temperature	Tbiv	-7	℃	For air-to-water heat pumps: Operation limit temperature	TOL	-10	℃
Cycling interval capacity for heating	Pcyc	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient (**)	Cdh	0.9	--	Heating water operating limit temperature	WTOL	65	℃
Power consumption in modes other than active mode				Supplementary heater			
Off mode	Poff	0.014	kW	Rated heat output (**)	Psup	1.69	kW
Standby mode	Psb	0.014	kW				
Thermostat-off mode	Pto	0.024	kW	Type of energy input Electrical			
Crankcase heater mode	Pck	0.000	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4030	m³/h
Sound power level, indoors/outdoors	LWA	42 ^a /59 40 ^b /59	dB	For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m³/h
Annual energy consumption	QHE	4056	kWh				
For heat pump combination heater:							
Declared load profile	L ^c /XL ^d			Water heating energy efficiency	ηwh	125 ^c /137 ^d	%
Daily electricity consumption	Qelec	3.78 ^c /5.67 ^d	kWh	Daily fuel consumption	Qfuel	-	kWh
Annual electricity consumption	AEC	820 ^c /1218 ^d	kWh	Annual fuel consumption	AFC	-	GJ
Contact details	GD Midea Heating & Ventilating Equipment Co. Ltd (Penglai industry road, Beijiao, Shunde, Foshan, Guangdong, P.R China)						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9. a) Represents : HB-A100/C***GN8-B2 b) Represents : HBT-A100/190CD***GN8-B2, HBT-A100/240CD***GN8-B2 c) Represents : HBT-A100/190CD***GN8-B2 d) Represents : HBT-A100/240CD***GN8-B2							